

# 10PR330

10" - 300W - 95 dB - 16 Ohm



## NOMINAL SPECIFICATIONS

Nominal Diameter	250 mm (10 in)
Overall Diameter	261 mm (10.28 in)
Bolt Circle Diameter	246 mm (9.69 in)
Baffle Cutout Diameter	230 mm (9.06 in)
Depth	111 mm (4.37 in)
Flange and Gasket Thickness	12 mm (0.47 in)
<b>Net Weight</b>	<b>4.1 kg (9.0 lb)</b>
Shipping Box (Single Carton Box)	282 x 280 x 140 mm (11.1 x 11.0 x 5.5 in)
Shipping Weight	4.7 kg (10.4 lb)

## PART NUMBER

Push Terminals - 16 Ohm Version 02504302

## NOTES:

- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
- (2) Maximum power is defined as 3dB greater than nominal power.
- (3) Treated Polycotton
- (4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$
- (5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	16 Ohm
Minimum Impedance	13.4 Ohm
AES Power Handling (1)	300 W
<b>Maximum Power Handling (2)</b>	<b>600 W</b>
<b>Sensitivity (1W/1m)</b>	<b>95 dB</b>
Frequency Range	60-3150 Hz
<b>Voice Coil Diameter</b>	<b>65 mm (2.56 in)</b>
Winding Material	Al
Former Material	Glass Fiber
Winding Depth	17.2 mm (0.68 in)
<b>Magnetic Gap Depth</b>	<b>8 mm (0.31 in)</b>
Flux Density	1.2 T
Magnet	Ferrite Ring
Basket Material	Aluminum
Demodulation	No
Cone Surround (3)	M-Roll
NET Air Volume filled by Loudspeaker	1.3 dm <sup>3</sup> (0.046 ft <sup>3</sup> )
Spider Profile	1x variable height waves

## THIELE & SMALL PARAMETERS

Fs	60 Hz
Re	11.3 Ohm
Qes	0.4
Qms	3.6
Qts	0.36
Vas	32.9 dm <sup>3</sup> (1.16 ft <sup>3</sup> )
Sd	348 cm <sup>2</sup> (53.89 in <sup>2</sup> )
Xmax (4)	7.27 mm
Xdamage (5)	15.25 mm
Mms	36.1 g
Bl	19.5 N/A
Le	1.12 mH
Mmd	28.8 g
Cms	0.19 mm/N
Rms	3.8 kg/s
Eta Zero	1.70 %
EBP	150 Hz

